Radio Interface of 5G New Radio

Marceau Coupechoux

3 Mar. 2021

Why 5G?

Some potential 5G applications :

Multimedia

- Ultra HD video
- Immersive and interactive experiences (AR/VR, virtual presence, tactile internet)
- Network games
- Live/streaming/on demand
- Collaborative productions, social networks
- Mobile and adaptive contents
- On demand networking (for temporary events)

Health

- · Tele-surgery
- Bio-connectivity: monitoring, diagnosis, treatment

- Wearable device communications
- Ambulance hospital
 communications

[Da Vinci]

Why 5G?



Image: Image:

Why 5G?



Intelligent Transport Systems

- Real-time control of vehicles
- Driver assistance
- Road traffic monitoring (floating car data)
- Accident prevention
- Remote vehicles diagnostics
- V2X communication
- Platooning
- Mobility support: high quality network access in buses, trains and airplanes

And many others that we don't even know today... For more information and references : [3GPP 22.891, 2016]

Outlines





3 Challenges







Outline

1 Introduction

2 Use cases classification

3 Challenges

- 4 Key enablers
- 5 5G NR radio interface

6 Conclusion

Use cases classification

Use cases classification



5G New Radio

MC

Use cases classification

The three typical use cases envisioned for 5G :

- eMBB (Enhanced Mobile Broadband) : Low latency, higher spectral efficiency/throughput.
- mMTC (massive Machine Type Communications) : Improved link budget, low device complexity, long device battery life (low energy consumption), support high density device deployment.
- URLLC (Ultra Reliable Low Latency Communications) : High reliability (low packet error rate), low latency.

We can add :

- eV2X (enhanced Vehicle to Everything) : High reliability, low latency, mobility.
- NETOP (network operation) : Flexibility, scalability, security, QoS, mobility.

Outline

- **1** Introduction
- 2 Use cases classification
- **3** Challenges
 - 4 Key enablers
 - **5 5G NR radio interface**

6 Conclusion

Challenges



See [ITU-R M.2410, 2017] for the complete list of requirements.

MC

3 Mar. 2021 10 / 83

Outline

- Introduction
- 2 Use cases classification
- 3 Challenges
- 4 Key enablers
 - **5** 5G NR radio interface

6 Conclusion

Massive MIMO

Massive MIMO = use >100 antennas to serve >10 users simultaneously on the same frequency. **Full Dimension MIMO** = beamform the signal in azimuth and elevation directions [Kammoun et al., 2019, Björnson et al., 2017, Marzetta, 2010].

- Advantages : high spectral and energy efficiency, simple linear precoding, the effects of noise and fading can be eliminated when the number of antennas is very large.
- Drawbacks/issues : antenna panel size, signalling for channel estimation, pilot contamination. Cell search, initial access and handovers requires a specific beam management.



Massive MIMO



[Nokia: 128 antenna elements at 2.5GHz]



[NEC: 360 antenna elements at 28GHz, height=30cm]

Massive MIMO

Hybrid beamforming : It is still not practical to have fully digital precoder in mm waves because a dedicated RF chain is required per antenna element (space, cost issues).



Typically :

- 3.5 GHz : 64 transceiver units, 128 antenna elements, mMIMO used for spatial multiplexing
- 28 GHz : 4 transceiver units, 512 or 1024 antenna elements, mMIMO used for beamforming

MC

3 Mar. 2021 14 / 83

Millimeter Waves = use spectrum bands above 6 GHz.

- Advantages : above 6 GHz (26+41+66), around 11 GHz are available (vs 1.2GHz below), small antennas for massive MIMO, few co-channel interference, can provide both backhaul and access links.
- Drawbacks/issues : difficult propagation conditions (high attenuation, blockage, absorption), baseband and RF processing, modelling and performance.



Large spectrum bands are available and antenna sizes are small (proportional to the wave length)





In mm waves, very large bandwidths are possible and the number of antennas can increase drastically



э

Channel characteristics at 28 GHz for a cell range of 200 m [Pi and Khan, 2011, Rappaport et al., 2013, Akdeniz et al., 2014] :

- There is a 20-25 dB loss compared to traditional cellular frequencies.
- Rain attenuation and atmospheric absorption characteristics have little impact on the path-loss (less than 2 dB and 0.02 dB resp.).
- Outdoor materials like tinted glass or brick pillars have high penetration losses (30-40 dB), while indoor materials (clear glass and drywall) have moderate losses (4 to 7 dB).
- Outdoor, the average path-loss exponent is 2.55 in LOS and 5.76 in NLOS.
- In NLOS, there are several multipath components at different angles of arrivals (typically 2 to 4 clusters), which makes beam combining and spatial multiplexing feasible.
- Foliage may have a significant impact depending of its depth.

See also [ITU-R M.2376, 2017] for technical feasibility and [ITU-R M.2412, 2017] for channel modeling.





Power Received at RX on corner of Greene and Broadway



FICURE 9. Polar plot showing the received power at a NLOS location. This plot shows an AOA measurement at the RX on Greene and Broadway from the TX on the five-story Kaufman building (78 m T-R separation). The polar plot shows here received power in dBm, the number of resolvable power inference, and RMS delay spread with varying RX azimuth angles [51].

In an NLOS dense urban environment, a coverage range of 200 m is possible provided that the net antenna gain is 49 dBi [Rappaport et al., 2013].



[Pi and Khan, 2011]

3 Mar. 2021 20

æ

20 / 83

Spectrum aggregation and unlicensed bands

Spectrum aggregation = aggregate carriers and technologies from both licensed and unlicensed spectrum. **Multi-RAT dual connectivity** = connect to different technologies from different nodes. Variants : intraband (contiguous or not), inter-band, only DL or both links.

- Advantages : high data rates when channel conditions are bad and MIMO is not efficient ; smooth integration with existing technologies ; better use of fragmented spectrum (truncking gain) ; load balancing.
- Drawbacks/issues : complex signalling and protocol aspects, tight cooperation between cells (joint scheduling); coexistence with other technologies, no QoS guarantee, regulatory requirements in unlicensed bands.



Spectrum aggregation and unlicensed bands

Channel Clear Assesment (CCA) and Listen-Before-Talk (LBT) operation :



Remarks :

- LTE-U (R12) : only DL; Licensed Assisted Access (LAA, R13) : only DL+LBT; eLAA (R14) :UL+DL; MulteFIRE : stand-alone LTE in unlicensed bands
- New Radio Unlicensed (NR-U) : foreseen for R16, priority on 5GHz and 60GHz bands, stand-alone operation

MC

∃ ▶ ∢

A B A A B A A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A
 A

Heterogeneous networks

Heterogenous networks = small cells, femto cells, relays complement the macro cell layer. They use multiple bands (incl. unlicensed) and multiple technologies.

- Advantages : increase network capacity (network densification), good channel conditions and low user sharing for high data rates.
- Drawbacks/issues : increase of interference, load balancing; site planning, sharing; regulation rules (EM exposure); backhaul availability; maintenance costs.



New waveform = CP-OFDM with flexible subcarrier spacing (SCS) and symbol duration.



Why again OFDM?

- High spectral efficiency.
- Low cost, low complexity, efficient equalization.
- Easy use of MIMO techniques because of its robustness wrt inter-symbol interference (ISI).
- Flexibility : it can support various services by appropriately designing subcarrier spacing, cyclic prefix length, user multiplexing.

However...

- OFDM has high PAPR, which implies a loss of power efficiency (not good for UL coverage and low cost small base stations). SC-FDMA has lower PAPR but is less flexible for scheduling, requires more complex MIMO receivers.
- OFDM is prone to inter-carrier interference (ICI) caused by [Zaidi et al., 2016] :
 - Doppler : the shift is increasing with carrier frequency and speed but decreases with subcarrier spacing. ICI power is proportional to the square of the normalized Doppler shift.

$$W_d = \frac{f_c v}{\Delta f \times c},\tag{1}$$

where f_c is the carrier frequency, v is the terminal speed, Δf is the subcarrier spacing and c is the speed of light.

• Phase noise : a random perturbation of the phase of the oscillator. It can be partly compensated by pilots. Related ICI power increases with carrier frequency but decreases with subcarrier spacing.

- The cyclic prefix represents a loss of efficiency. The delay spread is almost frequency independent (from less than 1 μ s in small cells, to a few μ s in urban areas). If we want to maintain a constant proportion of CP and still absorb the delay spread, we have an upper limit on the subcarrier spacing.
- Modulation/demodulation complexity increases with FFT size.

- URLLC : requires short symbols for low latency \Rightarrow large SCS
- eMBB : uses large bandwidths, requires not too large FFT \Rightarrow large SCS
- mmW : uses large bandwidths, inter-carrier interference increases with frequency but decreases with SCS ⇒ large SCS
- mMTC and sub-6GHz : smaller bandwidths and larger cells (more inter-symbol interference) ⇒ short SCS

	URLLC	eMBB	mMTC	mmW	Freq.<6GHz
Large SCS	\checkmark	\checkmark		\checkmark	
Short SCS			√		\checkmark

Table – Waveform design principles

Low latency = no fixed timing relations, dynamic TDD, self-contained slots, semi-persistent scheduling and grant free transmission, DL preemption of the ressources.



Dynamic TDD = a transmission can start at any OFDM symbol (this is the notion of "mini-slot" transmission).

- Advantages : allows very flexible scheduling, very fast ACK/NACK feedback, very low latencies. The flexible starting time is useful when listen-before-talk is used in unlicensed bands.
- Drawbacks/issues : may require additional signalling, creates new co-channel inter-cell interference issues.



A slot is made of 14 OFDM symbols.

Examples of slot formats (source : Ericsson) :

- (a) Heavy downlink transmission with uplink feedback.
- (b) Heavy uplink transmission with downlink feedback.
- (c) Very short time critical downlink transmission with immediate uplink ack (no need to wait for a slot boundary) or transmission in unlicensed band (transmit asap the channel is free) or in mmWaves (few symbols may carry sufficient volume of data).
- (d) Slot aggregation for heavy downlink transmission.



The slot format has an impact on several performance and planning aspects :

- DL/UL ratio : related to the amount of traffic in both directions.
- # of DL/UL switching points : more frequent switching points means lower latency, better channel estimation (positive impact, especially at high speed) and fast HARQ feedback. However, more guard periods are required and so more resources are lost.
- Coverage : large cells require long guard periods at every switching point.
- Coexistence : In France, the first deployment of 5G will be in the 3.5 GHz band. In order to avoid adjacent channel interference with LTE-TDD, slot format should be aligned between the two technologies.

Device-to-Device communications

Device to device = direct communications between terminals.

- Advantages : increase network capacity, low latency, good channel conditions for high data rates.
- Drawbacks/issues : increase of interference, resource management, signalling and synchronization.



Lean design

Lean design = minimize "always on" transmission

- Advantages : forward compatibility, energy saving.
- Drawbacks/issues : delays, loss of synchronization.

In LTE, there are always on signals like reference signals, synchronization signals, broadcast of system information. In NR : reference signals are sent only when needed, longer periodicity, new sleep modes, improved dependence on load [Frenger and Tano, 2019].



Virtualization

Virtualization = network functions are not anymore associated to a specific hardware, there are in programmable in software and located in a cloud made of generic hardware. Virtualization allows network slicing and mobile edge computing.

Network slice = a collection of network functions that support the communication requirements of particular uses case(s).

- Advantages : flexibility, scalability, isolation between slices.
- Drawbacks/issues : delays, security issues.



Virtualization

Mobile Edge Computing = signal processing, CPU and memory-intensive applications, caching is performed in an edge cloud; radio signal is carried over fiber to simple radio heads; coordination between antennas is made easier.


Outline

- **1** Introduction
- 2 Use cases classification
- 3 Challenges
- 4 Key enablers
- **5G NR radio interface**

6 Conclusion

Architecture



- Non Stand Alone (NSA) : Initial deployments, dual connectivity with LTE
- Stand Alone (SA) : After R16
- For more information : [3GPP 38.401, 2018]

э

Architecture



- A service based architecture.
- AMF : Access and Mobility, SMF : Session Mgt, PCF : Policy Control, NEF : Network Exposure, NRF : Network Repository, UDM : Unified Data Mgt, AUSF : Authentication Server, AF : Application Function, NSSF : Network Slice Selection
- For more information : [3GPP 23.501, 2018]

Protocol Stack



3 Mar. 2021 40 / 83

3

イロト イポト イヨト イヨト

Frequency bands

Two frequency bands are defined :

Table – NR Frequency bands and channel bandwidths

Designation	Frequency range
FR1	450 MHz - 6 GHz
FR2	24,25 GHz – 52,6 GHz

- FR1 is the classical frequency range for mobile communications (sub-6GHz band)
- FR2 is sometimes called mmWave (even if it is also dm wave)

Frequency bands and channel bandwidths

- There is a list of possible *operating bands*. Each operating band is characterized by a frequency range (FR1 or FR2), a UL/DL band, a duplex mode, applicable SCS and BS/UE bandwidths.
- Examples of operating bands in FR1 :

Designation	FR	UL [MHz]	DL [MHz]	Duplex mode
n66	FR1	1710 – 1780	2110 - 2200	FDD
n78	FR1	3300 - 3800	3300 - 3800	TDD
n261	FR2	27500-	TDD	

- Examples : In n66, subcarrier spacings 15, 30, and 60 kHz are applicable and BS/UE bandwidth are at most 40 MHz. In n78, same subcarrier spacings, BS/UE bandwidth up to 100 MHz. In n261, subcarrier spacing of 60 or 120 kHz, BS/UE bandwidth from 50 to 400 MHz.
- For more information : [3GPP 38.101, 2019, 3GPP 38.104, 2019]

Frequency bands and channel bandwidths

Although the standard defined a very wide range of possible bands, some are of particular interest (european perspective) :

- 700 MHz with maximum bandwidth of 20 MHz for coverage and/or machine-type communications.
- 1400 MHz only for downlink as a supplementary carrier for enhancing capacity.
- 3.4-3.8 GHz with maximum bandwidth of 100 MHz for capacity. The "core" band for 5G in early phases.
- 26 GHz with maximum bandwidth of 400 MHz for hot spots and small cells.
- Later : 42 GHz and 66-71 GHz.

Below 6 GHz, around 1.2 GHz may be available for mobile communications; above 6 GHz (26+41+66), around 11 GHz are available.

5G NR radio interface

Duplexing and multiplexing

- Duplexing will be mainly FDD below 6 GHz and TDD above. Small/isolated cell can adopt dynamic TDD, while macro cells semi-static TDD or FDD.
- Multiplexing is OFDMA for DL and UL with SC-FDMA as an option for UL (for coverage limited scenarios).



44 / 83

Modulations

• **Modulations** : up to 256QAM (in both DL and UL); $\pi/2$ -BPSK in UL for reduced PAPR and better amplifier efficiency at low data rates for IoT.



э

• • • • • • • • • • • • •

Coding

- Control channels : Reed-Muller block codes and CRC assisted polar codes [Arikan, 2009] (vs. tail-bitting convolutional codes in LTE).
- Data channels use rate compatible (for IR-HARQ) quasi-cyclic Low-Density Parity Check Codes (LDPC vs. Turbo codes in 3G, 4G).
- LDPC has been invented by Gallager in the 60's [Gallager, 1962], ignored for a long time and rediscovered in the 90's [MacKay and Neal, 1997].
- Already adopted in WiFi, DVB or ATSC.
- Compared to Turbo codes :
 - LDPC have usually similar performance but higher performance at high code rates
 - LDPC encoding and decoding is less complex
 - LDPC allow for a greater parallelism and thus lower decoding delay

[Richardson and Kudekar, 2018, Hui et al., 2018]

(日) (周) (日) (日)

Coding



Figure 1. Performance comparison between LDPC with sum-product (SP) decoding and LTE turbo with log-MAP decoding. Both are decoded using their optimal decoders with sufficiently large number of iterations. The plot highlights the fundamental differences in the code structure itself.

from [Richardson and Kudekar, 2018]

MC

Image: Image:

3 Mar. 2021 47 / 83

Coding



from [Richardson and Kudekar, 2018]

∃ ⊳

・ロト ・日本 ・日本

Numerology

- NR supports different subcarrier spacings to support different kinds of services.
- Different numerologies are derived from a base by a scaling factor. They are time aligned and the number of OFDM symbols per subframe is constant.
- The cyclic prefix overhead is approximately constant (about 6%), except for an extended prefix configuration at 60 kHz subcarrier spacing.
- It may be possible to multiplex different numerologies on the same carrier.
- Configurations :
 - $f_c < 6 \text{ GHz} : \mu \in \{0, 1, 2\}$ and bandwidth is from 5 MHz to 100 MHz
 - $f_c > 6 \text{ GHz}$: $\mu \in \{2,3\}$ and bandwidth is from 50 MHz to 400 MHz

Numerology

Table – Numerology	
--------------------	--

Subcarrier spacing config μ	0	1	2	3	4
Subcarrier spacing [kHz]	15	30	60	120	240
Symbol duration $[\mu s]$	66.7	33.3	16.6	8.33	4.17
Nominal cyclic prefix $[\mu s]$	4.7	2.41	1.205	0.6	0.3
Nominal max bandwidth [MHz]	49.5	99	188	396	397.4
Max FFT size	4096	4096	4096	4096	2048
Nb of symb/slot	14	14	14	14	14
Slot duration [ms]	1	0.5	0.25	0.125	0.0625
Frequency range	FR1	FR1	FR1/2	FR2	Only SSB

 $\mu \in \{0,1,3,4\}$ for PSS, SSS and PBCH, $\mu \in \{0,1,2,3\}$ for other channels. [3GPP 38.211, 2018]

3

< □ > < □ > < □ > < □ > < □ > < □ >

Frame Structure

- Regardless of the numerology, subframe and frame durations are constant (all numerologies align in time at subframe boundaries).
- The number of OFDM symbols per slot is always 14 for the normal prefix.



Resource Blocks and Resource Elements

- Resource Blocks are defined in the frequency domain as 12 consecutive subcarriers. There are bw 11 and 273 RBs (depending on the signal bandwidth).
- 1 RB during 1 OFDM symbol is called a Resource Element Group (REG).
- A Resource Element is defined as 1 subcarrier during 1 OFDM symbol on 1 antenna port for 1 subcarrier spacing configuration.



5G NR radio interface

Resource Blocks and Resource Elements

RB alignment across subcarrier spacings :



Image: A matrix and a matrix

-

3

Resource Blocks and Resource Elements

Frequency domain resource organization

- There is one resource grid per subcarrier spacing and antenna port.
- *Point A* is a reference point for all resource grids. Its location is signalled in SIB1.
- There are *common resource blocks* and *physical resource blocks* for every subcarrier spacing. CRB are a common reference; PRB are effectively used for transmissions in the bandwidth part.



Physical Channels



Sounding RS

э

A B A B A
A
B
A
A
B
A
A
B
A
A
B
A
A
B
A
A
B
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A
A

Transport Channels



∃ ⊳

э

Logical Channels



3 Mar. 2021 57 / 83

3

< □ > < □ > < □ > < □ > < □ > < □ >

Channel Mapping

МС



5G New Radio

∃ ⊳

< A

æ

Goal : acquiring time and frequency synchronisation, cell ID and system information

- 1 Find SSB in the synchronization raster
- 2 Get relative position of the SSB in the carrier bandwidth from PBCH
- 3 Get timing/beam index of the SSB from PBCH
- 4 Get initial CORESET from PBCH
- 5 Get SIB1 scheduling from CORESET

Example of channel and synchronization raster values around 3.5 GHz :



Synchronization blocks :



 PSS, SSS and PBCH are transmitted within a 'SS block' (SSB). SSBs are sent by bursts of up to 8 blocks (for FR1) or 64 blocks (FR2) within a half-frame of 5 ms and every 5 to 160 ms (ty pical : 20 ms).

MC

SS/PBCH :

- PSS is used for initial symbol boundary synchronization, PSS/SSS for the detection of the cell ID. PSS broadcasts 1 out 3 sequences and SSS one out of 336. There are in total 1008 possible cell IDs.
- Cell ID is required to decode PBCH and find DMRS locations.
- Subcarrier spacing for SSB can be higher than for data, e.g. 120/240 kHz iso 60/120 kHz in FR2 to reduce beam sweeping latency and overhead.
- MIB includes : SSB index (identifies this SSB in the SS burst set), half-frame indication, SFN, common subcarrier spacing, frequency offset bw this SSB and the overall resource block grid, info for decoding PDCCH/SIB1 (bandwidth, CORESET, common search space, PDCCH parameters).
- PBCH has its own reference signals DMRS.

Random access

- The PRACH resources and the preamble format to be used are provided to the UE in the system information.
- Open loop power control and power ramping are applied.



Data transmission : BWP

Bandwidth Parts (BWP) : "Stay in the box" !

- A UE can be active only on a narrow part of the NR carrier bandwidth (e.g. to reduce energy consumption or for low-end devices).
- With bandwidth adaptation, the receive and transmit bandwidth of a UE can be adjusted :
 - the width (e.g. the BWP can shrink in case of low activity to save power)
 - the location (to increase scheduling flexibility)
 - the subcarrier spacing (to adapt to different services)
- BWPs are configured at the UE. The network can inform the UE to dynamically change its active BWP.



5G NR radio interface

Data transmission : DL control

Control Resource Sets (CORESETs) :



- A CORESET is a time-frequency resource where control channels PDCCH may be located. Contrary to LTE, it does not span the entire bandwidth.
- The location and the size of the CORESETs are semi-statically configured by RRC. Rather at the beginning of the slot but not necessary (for ultra low latency).
- Different code rates are available by aggregating CCEs.

5G NR radio interface

Data transmission : UL control

PUCCH :

- Localization is flexible in time and frequency : either predefined formats are signalled by SIB1 or defined by RRC messages.
- UCI include CQI, ACK/NACK and scheduling requests.



Reference Signals

Demodulation Reference Signals (DMRS) for coherent demodulation.

- Support variable nb. of antenna ports, very short transmissions, high-speed scenarios
- Front-loaded : the receiver can decode on the fly for lower latency
- DMRS at the beginning of the slot : PDSCH occupies most of the slot
- DMRS at the beginning of the transmission : PDSCH short transmissions





DMRS position relative to transmission start

One slot = 14 OFDM symbols

Reference Signals

Channel State Information Reference Signals (CSI-RS) for channel sounding on the DL

- Configured on a per-UE basis to avoid "always on" signals.
- Several UEs share the same set of CSI-RS.
- CSI-RS for different antenna ports are multiplexed in time, frequency or code
- Periodic, semi-persistent (may desactivated) or aperiodic (the UE is informed)



MC

Reference Signals

Other reference signals :

- PTRS are used for tracking the phase of the local oscillator at transmitter and receiver. This is used to compensate for phase noise and it is particularly important at high carrier frequencies.
- SRS are used for UL sounding.

Some words on future releases

R16 for beg. of 2020 (R17 for end of 2021).

VERTICALS	SYSTEM
	IMPROVEMENTS
V2X	
Industrial IoT	Unlicensed bands
URLLC	Enhancements for eMBB

- V2X : platooning, extended sensors, automated driving, remote driving.
- IIoT and URLLC : for factory automation with the goal of replacing wired Ethernet
- Unlicensed bands : LAA and standalone operation
- eMBB enhancements : positioning, MIMO, power consumption, dual connectivity, SON, interference mitigation, mobility, etc.

[3GPP 21.916, 2019, Balazs Bertenyi, 2019]

Some words on future releases

R17 expected for end of 2021. Some potential work areas (decisions in Dec 2019) :

- NR light for mid-tier devices
- NR above 52.6GHz with decision on waveform
- Multi-SIM operation
- NR multicast and broadcast mainly for V2X and public safety
- NR for non terrestrial networks
- Data collection to enable AI and SON
- Enhancements in small data transfer, D2D, coverage, IoT, URLLC, MIMO, integrated access and backhaul.

[Balazs Bertenyi, 2019]

Outline

- **1** Introduction
- 2 Use cases classification
- 3 Challenges
- 4 Key enablers
- 5 5G NR radio interface


Towards 6G?

Some possible hot topics to imagine 6G :

- THz communications
- Visible light communications
- Cell-less architectures
- Intelligent meta-surfaces
- Zero-battery devices and wireless transfer
- ML physical layer design
- ML based resource allocation
- AI based network optimization

6G for what? Telepresence? What about energy consumption?

References I

[3GPP 21.916, 2019] 3GPP 21.916 (2019).

3GPP TS 21.916 : Release 16 Description ; Summary of Rel-16 Work Items .

[3GPP 22.891, 2016] 3GPP 22.891 (2016).

3GPP TS 22.891 : Feasibility Study on New Services and Markets Technology Enablers.

[3GPP 23.501, 2018] 3GPP 23.501 (2018).

3GPP TS 23.501 : System Architecture for the 5G System.

[3GPP 38.101, 2019] 3GPP 38.101 (2019).

3GPP TS 38.101 : User Equipment (UE) radio transmission and reception.

[3GPP 38.104, 2019] 3GPP 38.104 (2019).

3GPP TS 38.104 : Base Station (BS) radio transmission and reception.

[3GPP 38.211, 2018] 3GPP 38.211 (2018).

3GPP TS 38.211 : Physical channels and modulation.

References II

[3GPP 38.401, 2018] 3GPP 38.401 (2018).

3GPP TS 38.401 : NG-RAN; Architecture Description.

[Akdeniz et al., 2014] Akdeniz, M. R., Liu, Y., Samimi, M. K., Sun, S., Rangan, S., Rappaport, T. S., and Erkip, E. (2014).

Millimeter wave channel modeling and cellular capacity evaluation.

IEEE journal on selected areas in communications, 32(6) :1164–1179.

[Arikan, 2009] Arikan, E. (2009).

Channel polarization : A method for constructing capacity-achieving codes for symmetric binary-input memoryless channels.

IEEE Transactions on information Theory, 55(7) :3051–3073.

[Balazs Bertenyi, 2019] Balazs Bertenyi (2019).

RAN Rel-16 progress and Rel-17 potential work areas.

References III

[Björnson et al., 2017] Björnson, E., Hoydis, J., Sanguinetti, L., et al. (2017).
 Massive mimo networks : Spectral, energy, and hardware efficiency.
 Foundations and Trends® in Signal Processing, 11(3-4) :154–655.

[Frenger and Tano, 2019] Frenger, P. and Tano, R. (2019).

More capacity and less power : How 5g nr can reduce network energy consumption. In 2019 IEEE 89th Vehicular Technology Conference (VTC2019-Spring), pages 1–5. IEEE.

[Gallager, 1962] Gallager, R. (1962).

Low-density parity-check codes.

IRE Transactions on information theory, 8(1) :21–28.

[Hui et al., 2018] Hui, D., Sandberg, S., Blankenship, Y., Andersson, M., and Grosjean, L. (2018).

Channel coding in 5g new radio : A tutorial overview and performance comparison with 4g lte.

ieee vehicular technology magazine, 13(4) :60-69.

MC

イロト イポト イヨト イヨト

References IV

[ITU-R M.2376, 2017] ITU-R M.2376 (2017).

ITU-R M.2376 : Technical feasibility of IMT in bands above 6 GHz.

[ITU-R M.2410, 2017] ITU-R M.2410 (2017).

ITU-R M.2410 : Minimum requirements related to technical performance for IMT-2020 radio interface(s).

[ITU-R M.2412, 2017] ITU-R M.2412 (2017).

 $\mathsf{ITU}\text{-}\mathsf{R}$ M.2412 : Guidelines for evaluation of radio interface technologies for $\mathsf{IMT}\text{-}2020.$

[Kammoun et al., 2019] Kammoun, A., Alouini, M.-S., et al. (2019).

Elevation beamforming with full dimension mimo architectures in 5g systems : A tutorial.

IEEE Communications Surveys & Tutorials.

References V

[MacKay and Neal, 1997] MacKay, D. J. and Neal, R. M. (1997). Near shannon limit performance of low density parity check codes. *Electronics letters*, 33(6) :457–458.

[Marzetta, 2010] Marzetta, T. L. (2010).

Noncooperative cellular wireless with unlimited numbers of base station antennas. *IEEE transactions on wireless communications*, 9(11) :3590–3600.

[Pi and Khan, 2011] Pi, Z. and Khan, F. (2011).

An introduction to millimeter-wave mobile broadband systems.

IEEE communications magazine, 49(6) :101–107.

[Rappaport et al., 2013] Rappaport, T. S., Sun, S., Mayzus, R., Zhao, H., Azar, Y., Wang, K., Wong, G. N., Schulz, J. K., Samimi, M., and Gutierrez, F. (2013).
Millimeter wave mobile communications for 5g cellular : It will work! *IEEE access*, 1 :335–349.

(日) (周) (日) (日)

References VI

- [Richardson and Kudekar, 2018] Richardson, T. and Kudekar, S. (2018). Design of low-density parity check codes for 5g new radio. *IEEE Communications Magazine*, 56(3) :28–34.
- [Zaidi et al., 2016] Zaidi, A. A., Baldemair, R., Tullberg, H., Bjorkegren, H., Sundstrom, L., Medbo, J., Kilinc, C., and Da Silva, I. (2016).
 Waveform and numerology to support 5g services and requirements.
 IEEE Communications Magazine, 54(11) :90–98.

Acronyms I

5GC	5G Core Network
ACK	Acknowledgment
AI	Artificial Intelligence
AM	ARQ Acknowledged Mode
ARFCN	Absolute Radio Frequency Channel Number
AR/VR	Augmented/Virtual Reality
ATSC	Advanced Television Systems Committee
BCCH	Broadcast Control Channel
BCH	Broadcast Channel
BS	Base Station
BWP	Bandwidth Part
CCA	Channel Clear Assessment
CCCH	Common Control Channel
CCE	Control Channel Element
CP	Cyclic Prefix
CQI	Channel Quality Indicator
CRB	Common Resource Block
CSI	Channel State Information
CU	Central Unit
D2D	Device to Device
DMRS	Demodulation Reference Signal
DCCH	Dedicated Control Channel
DCI	Downlink Control Information
DL	Downlink
DL-SCH	Downlink Shared Channel
DTCH	Dedicated Traffic Channel
DU	Distributed Unit
DVB	Digital Video Broadcasting

5G New Radio

3 Mar. 2021 80 / 83

3

Acronyms II

EM	Electromagnetic
EPC	Evolved Packet Core
FDD	Frequency Division Duplex
FFT	Fast Fourier Transform
GSCN	Global Synchronization Channel Number
HARQ	Hybrid Automatic Repeat on Request
ICI	Inter-Carrier Interference
IIoT	Industrial IoT
loT	Internet of Things
IR	Incremental Redundancy
ISI	Inter-Symbol Interference
LAA	Licensed Assisted Access
LBT	Listen Before Talk
LDPC	Low Density Parity Check
LOS	Line of Sight
LTE	Long Term Evolution
MAC	Medium Access Control
MBB	Mobile Broadband
MIMO	Multiple Input Multiple Output
ML	Machine Learning
mmW	Millimeter Waves
MTC	Machine-Type Communications
NACK	Negative Acknowledgment
NB	Node-B
NLOS	Non Line of Sight
NR	New Radio
NSA	Non Stand Alone
OFDM	Orthogonal Frequency Division Multiplex
OFDMA	Orthogonal Frequency Division Multiple Access

글 🕨 🛛 글

Conclusion

Acronyms III

PAPR	Peak to Average Power Ratio
PBCH	Physical Broadcast Channel
PCCH	Paging Control Channel
PCH	Paging Channel
PDCCH	Physical Downlink Control Channel
PDCP	Packet Data Convergence Protocol
PDSCH	Physical Downlink Shared Channel
PDU	Protocol Data Unit
PMR	Professional Mobile Radio
PRACH	Physical Random Access Channel
PRB	Physical Resource Block
PSS	Primary Synchronization Signal
PTRS	Phase Tracking Reference Signal
PUCCH	Physical Uplink Control Channel
PUSCH	Physical Uplink Shared Channel
QAM	Qadrature Amplitude Modulation
QoS	Quality of Service
RACH	Random Access Channel
RAN	Radio Access Network
RAT	Radio Access Technology
RB	Resource Block
RE	Resource Element
REG	Resource Element Group
RLC	Radio Link Control
ROHC	Robust Header Compression
RRC	Radio Resource Control
RS	Reference Signal
SA	Stand Alone
SC-FDMA	Single Carrier Frequency Division Multiple Access

æ

Acronyms IV

SCS	Subcarrier Spacing
SDAP	Service Data Adaptation Protocol
SDU	Service Data Unit
SIB	System Information Block
SON	Self-Organized Networks
SRS	Sounding Reference Signal
SSB	Synchronization Signal Block
SSS	Secondary Synchronization Signal
TCP	Transport Control Protocol
TDD	Time Division Duplex
TM	ARQ Transparent Mode
TTI	Transmission Time Interval
UCI	Uplink Control Information
UE	User Equipment
UM	ARQ Unacknowledged Mode
UL	Uplink
UL-SCH	Uplink Shared Channel
UPF	User Plane Function
URLLC	Ultra Reliable Low Latency Communications
V2X	Vehicle to Everything

글 🛌 😑

・ロト ・ 日下 ・ 日下